Operation Guide ANA(3H3E-1) CASIO

Your watch may differ somewhat from the one shown in the


Notes

- Some water resistant models are equipped with a screw lock crown.
- with a screw lock crown.

 With such models, you must unscrew the crown in the direction noted in the illustration to loosen it before you can pull it out. Do not pull too forcibly on such crowns.

 Also note that such watches are not water resistant while their crowns are loosened. Be
- sure to screw the crowns back in as far as they will go after making any setting.





■ For watch with the elapsed time bezel Rotate the elapsed time bezel Rotate the elapsed time bezel to align the $\overline{\mathbb{V}}$ mark with the minute hand. After certain amount of time elapsed, read the graduation on the elapsed time bezel which the minute hand points to. The elapsed time is indicated.



Click 1 (Day setting)

Click 2 (Time and day of wee setting)

Elapsed time beze

| Specifications | | | | |
|----------------|------------|-----------------------------------|--------------|-----------------|
| | Module No. | Accuracy at normal temperature | Battery type | Battery life |
| | 1343 | ±20 seconds per month | SR916SW | Approx. 3 years |
| | 1794/2364 | ±20 seconds per month | SR621SW | Approx. 2 years |
| | 5071/5072 | ±20 seconds per month | SR621SW | Approx. 3 years |
| | 5224 | ±20 seconds per month | SR920SW | Approx. 3 years |